

# CS 473: Algorithms, Fall 2010

## HW 2 (due Tuesday, September 14th)

This homework contains four problems. **Read the instructions for submitting homework on the course webpage.** In particular, *make sure* that you write the solutions for the problems on separate sheets of paper. Write your name and netid on each sheet.

**Collaboration Policy:** For this home work, Problems 2-4 can be worked in groups of up to 3 students each.

**Problem 1 should be answered in Compass as part of the assessment HW2-Online and should be done individually.**

1. (10 pts) Short questions to be answered on compass individually.
2. (30 pts) Suppose you are given a directed graph  $G = (V, E)$  with non-negative edge lengths;  $\ell(e)$  is the length of  $e \in E$ . You are interested in the shortest path distance between two given locations/nodes  $s$  and  $t$ . It has been noticed that the existing shortest path distance between  $s$  and  $t$  in  $G$  is not satisfactory and there is a proposal to add exactly one edge to the graph to improve the situation. The candidate edges from which one has to be chosen is given by  $E' = \{e_1, e_2, \dots, e_k\}$  and you can assume that  $E \cap E' = \emptyset$ . The length of the  $e_i$  is  $\alpha_i \geq 0$ . Your goal is figure out which of these  $k$  edges will result in the most reduction in the shortest path distance from  $s$  to  $t$ . Describe an algorithm for this problem that runs in time  $O((m + n) \log n + k)$  where  $m = |E|$  and  $n = |V|$ . Note that one can easily solve this problem in  $O(k(m + n) \log n)$  by running Dijkstra's algorithm  $k$  times, one for each  $G_i$  where  $G_i$  is the graph obtained by adding  $e_i$  to  $G$ .
3. (30 pts) Given a directed graph  $G = (V, E)$  and two nodes  $s, t$ , an  $s$ - $t$  walk is a sequence of nodes  $s = v_0, v_1, \dots, v_k = t$  where  $(v_i, v_{i+1})$  is an edge of  $G$  for  $0 \leq i < k$ . Note that a node may be visited multiple times in a walk — this is how it differs from a path. Given  $G, s, t$  and an integer  $k \leq n$ , design a linear time algorithm to check if there is an  $s$ - $t$  walk in  $G$  that visits at least  $k$  *distinct* nodes including  $s$  and  $t$ .
  - Solve the problem when  $G$  is a DAG. *Hint:* Can you find a longest path in a DAG?
  - Solve the problem when  $G$  is an arbitrary directed graph. *Hint:* If  $G$  is strongly connected then there is always such a walk even for  $k = n$  (do you see why?).
4. (30 pts) Let  $G = (V, E)$  be a directed graph with edge lengths that can be negative. Let  $\ell(e)$  denote the length of edge  $e \in E$  and assume it is an integer. Assume you have a shortest path tree  $T$  rooted at a source node  $s$  that contains all the nodes in  $V$ . You also have the distance values  $d(s, u)$  for each  $u \in V$  in an array (thus, you can access the distance from  $s$  to  $u$  in  $O(1)$  time). Note that the existence of  $T$  implies that  $G$  does not have a negative length cycle.
  - Let  $e = (p, q)$  be an edge of  $G$  that is *not* in  $T$ . Show how to compute in  $O(1)$  time the smallest integer amount by which we can decrease  $\ell(e)$  before  $T$  is not a valid shortest path tree in  $G$ .

- Let  $e = (p, q)$  be an edge in the tree  $T$ . Show how to compute in  $O(m + n)$  time the smallest integer amount by which we can increase  $\ell(e)$  such that  $T$  is no longer a valid shortest path tree. Your algorithm should output  $\infty$  if no amount of increase will change the shortest path tree.

The example below may help you. The dotted edges form the shortest path tree  $T$  and the distances to the nodes from  $s$  are shown inside the circles. For the first part consider an edge such as  $(b, d)$  and for the second part consider an edge such as  $(f, e)$ .

