

Possibly Useful Formulas

Probability:

$$P(X = x) = \Pr(X = x) \text{ or } P(X = x) = \frac{d}{dx} \Pr(X \leq x)$$

$$P(X, Y) = P(X|Y)P(Y)$$

$$E[f(X, Y)] = \sum_{x, y} f(x, y)P(X = x, Y = y)$$

$$\text{MAP Decision: } f(x) = \underset{y}{\operatorname{argmax}} P(Y = y|X = x)$$

$$\text{Bayes Error Rate: } = \sum_x P(X = x) \min_y P(Y \neq y|X = x)$$

$$\text{Precision} = P(Y = 1|f(X) = 1) = \frac{TP}{TP + FP}$$

$$\text{Recall=Sensitivity} = P(f(X) = 1|Y = 1) = \frac{TP}{TP + FN}$$

$$\text{Specificity} = P(f(X) = 0|Y = 0) = \frac{TN}{TN + FP}$$

$$\text{Naive Bayes: } f(x) \approx \underset{y}{\operatorname{argmax}} \left(\ln P(Y = y) + \sum_{i=1}^n \ln P(W = w_i|Y = y) \right)$$

$$\text{Laplace Smoothing: } P(W = w_i|Y = y) = \frac{k + \text{Count}(w_i, y)}{k + \sum_{v \in \mathcal{Y}} (k + \text{Count}(v, y))}$$

$$\text{HMM: } v_1(j) = \pi(j)b_j(\mathbf{x}_1)$$

$$v_t(j) = \max_i v_{t-1}(i)a_{i,j}b_j(\mathbf{x}_t), \quad \psi_t(j) = \underset{i}{\operatorname{argmax}} v_{t-1}(i)a_{i,j}b_j(\mathbf{x}_t)$$

$$y^*(T) = \underset{i}{\operatorname{argmax}} v_T(i), \quad y^*(t) = \psi_{t+1}(y^*(t+1))$$

$$\text{Demographic Parity: } P(f(X)|A = 1) = P(f(X)|A = 0)$$

$$\text{Equal Odds: } P(f(X)|Y, A = 1) = P(f(X)|Y, A = 0)$$

$$\text{Predictive Parity: } P(Y|f(X), A = 1) = P(Y|f(X), A = 0)$$

$$\text{Learning: } \mathcal{R} = E[\ell(Y, f(X))], \quad \mathcal{R}_{emp} = \frac{1}{n} \sum_{i=1}^n \ell(y_i, f(x_i))$$

$$\text{Linear Regression: } f(\mathbf{x}) = \mathbf{w}^T \mathbf{x} + b$$

$$\mathcal{L} = \frac{1}{n} \sum_{i=1}^n \mathcal{L}_i, \quad \mathcal{L}_i = \frac{1}{2} \varepsilon_i^2, \quad \varepsilon_i = f(\mathbf{x}_i) - y_i$$

Linear Classifier: $f(\mathbf{x}) = \operatorname{argmax}(\mathbf{W}\mathbf{x} + \mathbf{b})$

Perceptron: $\mathbf{w}_c \leftarrow \begin{cases} \mathbf{w}_c - \eta \mathbf{x} & c = \operatorname{argmax}(\mathbf{W}\mathbf{x} + \mathbf{b}) \\ \mathbf{w}_c + \eta \mathbf{x} & c = y \\ \mathbf{w}_c & \text{otherwise} \end{cases}$

Softmax: $f_c(\mathbf{x}) = \frac{\exp(\mathbf{w}_c^T \mathbf{x} + b_c)}{\sum_{k=1}^{|\mathcal{Y}|} \exp(\mathbf{w}_k^T \mathbf{x} + b_k)} \approx P(Y = c | \mathbf{x})$

Sigmoid: $\sigma(\mathbf{w}^T \mathbf{x} + b) = \frac{1}{1 + e^{-(\mathbf{w}^T \mathbf{x} + b)}} \approx P(Y = 1 | \mathbf{x})$

Cross Entropy: $\mathcal{L} = -\ln f_y(\mathbf{x}), \frac{\partial \mathcal{L}}{\partial f_c(\mathbf{x})} = \begin{cases} -\frac{1}{f_c(\mathbf{x})} & c = y \\ 0 & \text{otherwise} \end{cases}$

SGD: $\mathbf{w}_c \leftarrow \mathbf{w}_c - \eta \frac{\partial \mathcal{L}}{\partial \mathbf{w}_c} = \begin{cases} \mathbf{w}_c - \eta (f_c(\mathbf{x}_i) - 1) \mathbf{x}_i & c = y \\ \mathbf{w}_c - \eta (f_c(\mathbf{x}_i) - 0) \mathbf{x}_i & \text{otherwise} \end{cases}$

Pinhole Camera: $\frac{x'}{f} = -\frac{x}{z}, \frac{y'}{f} = -\frac{y}{z}$

Image Gradient:

$$h_x(x', y') = \frac{h(x' + 1, y') - h(x' - 1, y')}{2}, \quad h_y(x', y') = \frac{h(x', y' + 1) - h(x', y' - 1)}{2}$$

Convolution:

$$y[k, l] = \sum_i \sum_j x[k - i, l - j] h[i, j], \quad \frac{\partial y[k, l]}{\partial h[i, j]} = x[k - i, l - j]$$

Max Pooling:

$$z[m] = \max_{(m-1)p+1 \leq k \leq mp} y[k], \quad \frac{\partial z[m]}{\partial y[j]} = \begin{cases} 1 & j = \operatorname{argmax}_{(m-1)p+1 \leq k \leq mp} y[k] \\ 0 & \text{otherwise} \end{cases}$$

Admissible: $\hat{h}(n) \leq h(n)$

Consistent: $\hat{h}(n) - \hat{h}(m) \leq h(n, m)$

Value Iteration: $u_i(s) = r(s) + \gamma \max_a \sum_{s'} P(s'|s, a) u_{i-1}(s)$

Policy Evaluation: $u_\pi(s) = r(s) + \gamma \sum_{s'} P(s'|s, \pi(s)) u_\pi(s')$

Policy Improvement: $\pi_{i+1}(s) = \operatorname{argmax}_a \sum_{s'} P(s'|s, a) u_{\pi_i}(s')$

Alpha-Beta Max Node: $v = \max(v, \text{child}); \quad \alpha = \max(\alpha, \text{child})$

Alpha-Beta Min Node: $v = \min(v, \text{child}); \quad \beta = \min(\beta, \text{child})$

Expectiminimax: $u(s) = \begin{cases} \max_a \sum_{s'} P(s'|a, a) u(s') & s \in \text{max states} \\ \min_a \sum_{s'} P(s'|a, a) u(s') & s \in \text{min states} \end{cases}$

Mixed Nash Equilibrium: $P(A=0)r_B(0,0) + P(A=1)r_B(1,0) = P(A=0)r_B(0,1) + P(A=1)r_B(1,1)$
 $P(B=0)r_A(0,0) + P(B=1)r_A(0,1) = P(B=0)r_A(1,0) + P(B=1)r_A(1,1)$

Unification: $S: \{\mathcal{Y}_P, \mathcal{Y}_Q\} \rightarrow \{\mathcal{Y}_Q, \mathcal{C}\}$ such that $S(P) = S(Q) = U$

CBOW Generative: $\mathcal{L} = -\frac{1}{T} \sum_{t=1}^T \sum_{j=-c, j \neq 0}^c \ln \frac{\exp(\mathbf{v}_t^T \mathbf{v}_{t+j})}{\sum_{\mathbf{v} \in \mathcal{V}} \exp(\mathbf{v}^T \mathbf{v}_{t+j})}$

Skip-gram Contrastive: $\mathcal{L} = -\frac{1}{T} \sum_{t=1}^T \left(\sum_{\mathbf{v}' \in \mathcal{D}_+(w_t)} \ln \frac{1}{1 + e^{-\mathbf{v}'^T \mathbf{v}_t}} + \sum_{\mathbf{v}' \in \mathcal{D}_-(w_t)} \ln \frac{1}{1 + e^{\mathbf{v}'^T \mathbf{v}_t}} \right)$

Transformer: $\mathbf{c}_t = \sum_s \alpha(t, s) \mathbf{v}_s$

Attention: $\alpha(t, s) = \frac{\exp(\mathbf{q}_t^T \mathbf{k}_s)}{\sum_{s'} \exp(\mathbf{q}_t^T \mathbf{k}_{s'})}$

Model-based Learning: $P(s_{t+1}|s_t, a_t) = \frac{\text{Count}(s_t, a_t, s_{t+1}) + k}{\sum_{s' \in \mathcal{S}} (\text{Count}(s_t, a_t, s') + k)}$

On-policy learning: $\mathbf{W}_{a_t} \leftarrow \mathbf{W}_{a_t} + \eta \nabla_{\mathbf{W}_{a_t}} \ln P(s_{t+1}|s_t, a_t)$

Off-policy learning: $\mathbf{W} \leftarrow \mathbf{W} + \eta \nabla_{\mathbf{W}} \ln P(s_{t+1}|s_t, a_t)$

Epsilon-first: $N_{\text{first}} = \frac{1}{\epsilon}$

Epsilon-greedy: If $z \leq \epsilon$ then explore, $z \in (0, 1)$

TD-learning: $q_{\text{local}}(s_t, a_t) = r_t + \gamma \max_{a' \in \mathcal{A}} q_t(s_{t+1}, a')$

SARSA: $q_{\text{local}}(s_t, a_t) = r_t + \gamma q_t(s_{t+1}, a_t + 1)$

Q-learning: $q_{t+1}(s_t, a_t) = q_t(s_t, a_t) + \eta (q_{\text{local}}(s_t, a_t) - q_t(s_t, a_t))$

Deep Q: $\theta_{t+1} = \theta_t - \eta \frac{\partial}{\partial \theta} \frac{1}{2} (q_t(s_t, a_t) - q_{\text{local}}(s_t, a_t))^2$

Policy Gradient: $\frac{\partial u(s_t)}{\partial \theta} = \sum_{\tau} \frac{\partial P(\tau)}{\partial \theta} v(\tau) = \sum_{\tau} P(\tau) \frac{\partial \ln P(\tau)}{\partial \theta} v(\tau) = E \left[\frac{\partial \ln P(\tau)}{\partial \theta} v(\tau) \right]$

Standard error: $M = \frac{1}{n} \sum_{i=1}^n Y_i, \quad \text{stdev}(M) = \frac{\sigma}{\sqrt{n}}$